
F A X C O V E R S H E E T

To: Test

From: Test

Company: Test

Company: Test

Fax: 19725329272

Phone: Test

Date: 01/14/2026 10:28:35

Pages: 2 (w/coversheet)

Subject: Test

Message: Test

<<NETWORK CONFIGURATION>>

```

<Interface>                WirelessLAN on
<Node Type>                 Brother NC-8500w, IEEE 802.11b/g/n (Active)
<Node Firmware Ver.>       Firmware Ver.ZN (Feb 11 2021 11:01:16)
<MAC Address>              cc-6b-1a-07-5c-28
<Node name>                BRWCC6B1E075C28

<Active services>         BRNB422004A12EF
                           BINARY_P1
                           TEXT_P1
                           POSTSCRIPT_P1
                           PCL_P1
                           BRNB422004A12EF_AT

```

```

<Protocols>
TCP/IP          on      IPv6          off      NetBIOS/IP      on
APIPA          on      WebBasedManagement on      Telnet          off
SNMP           on      Remote Setup    on      Syslog          off
LPD            on      Raw Port        on      IPP             on
WebServices    on      Network scan    on      PC fax receive  on
POP3/IMAP4/SMT on      FTPServer       off     FTPClient       on
TFTP           on      CIFS            on      mDNS            on
LLMNR          on      LDAP            on      SNMP            on
Proxy          off     SFTP            on      AirPrint        on
Google Cloud Print on    WebDAV          on      Universal Print off

```

```

<IP Settings>
IP Address      10.29.2.226 (via DHCP)
Subnet Mask     255.255.255.0
IP Gateway      10.29.2.1
Boot Method     AUTO
Boot Tries      3
IP Filter       Disabled

```

```

GW Timeout (sec) 21
DNS Address Config AUTO
Primary DNS Server 10.29.2.1
Secondary DNS Server 0.0.0.0

```

```

<NetBIOS Name>      BRWCC6B1E075C28
<WINS Address Config> AUTO
<Primary WINS Server> 0.0.0.0
<Secondary WINS Server> 0.0.0.0

```

```

<Send E-mail Settings(SMTP)>
Device Mail Address brnb422004a12ef@example.com
Server              0.0.0.0
Port                25
<Receive E-mail Setting(POP3/IMAP4)>
Protocol            POP3
Server              0.0.0.0
Port                110
Polling Freq. (sec) 600

```

```

<mDNS Service Name> Brother MFC-L6900DW series

```

```

<WebServices Name> Brother MFC-L6900DW series [b422004a12ef]

```

```

<Certificate>
Status          None

```

```

<SNMP Settings>
Communication Mode v1/v2c(RW)

```

```

<Comm. Mode>        Infrastructure
<Name(SSID)>        EpiphanyDermatology
<Authentication Mode> WPA/WPA2-PSK
<Encryption Mode>    AES
<Wireless Link Status> Link OK, 11n(72Mbps), Receiving Signal=3, Operating Ch=6
<Tx Power Code>     Full, 227, 0, 0

```

```

<Network Statistics>
Packets Received    53434
Bytes Received      12921467
Packets Transmitted 21223
Bytes Transmitted   2691412

<Wireless Statistics>
RX Frames Received OK      53311
RX Frames Error            1
TX Frames Transmitted OK   13617
TX Frames Error            1

```

```

<Default Password>
Pwd:                ds->pLG%

```