

Jan. 27, 2026 02:03 PM (page 2)

RICOH MP 6055 Configuration Page / Network Control System 16.60

[SMB]

Current Path Name : \\RNP002673DAC5E1\MP6055
 Client port : 445
 Client auth level : 2 (NTLMv2->NTLM/LM)
 Client MSD browse : Off
 Client write mode : Async
 Client v3 : On
 Client Share Access : On(Read/Write)

[SSDP]

Advertise : On
 UUID : 51d921a8-5a4a-11e7-ba7f-f90c143bfdee
 Profile : 10000(s)
 TTL : 4

[UPnP]

URL :

[SNMP]

Supported Protocol : IPv4:On, IPv6:On
 Supported Version : SNMPv1v2:On, SNMPv3:On
 Trap : v1Trap:On, v2Trap:Off, v3Trap:Off
 SNMPv1v2 Remote Setting : Enable
 SNMPv3 Privacy Mode : Auto
 Context Name : GWNCS

[Security]

Security Mode Level : Custom
 Certificate Verification:Off

[Print Job Authentication Free]

IPv4 Address Settings
 [1] 0.0.0.0 - 0.0.0.0
 [2] 0.0.0.0 - 0.0.0.0
 [3] 0.0.0.0 - 0.0.0.0
 [4] 0.0.0.0 - 0.0.0.0
 [5] 0.0.0.0 - 0.0.0.0
 Interface Settings :

[SSL Cipher Strength]

SSL/TLS Configure : Ciphertext/Cleartext
 SSL Protocol
 TLS1.2:Up TLS1.1:Up TLS1.0:Up SSL3.0:Down
 Cipher Suite
 AES 256bit:On AES 128bit:On 3DES 168bit:On RC4 128bit:Off

[Kerberos Authentication]

Cipher Suite
 AES256-CTS-HMAC-SHA1-96:On AES128-CTS-HMAC-SHA1-96:On
 DES3-CBC-SHA1:On RC4-HMAC:On DES-CBC-MD5:On

[NAT]

Port Forwarding(IPv4) : On
 Port Forwarding(IPv6) : On