

KONICA MINOLTA C250i

Configuration Page

Print Operation Menu Map

Basic Setting

Default Paper Size = 8 1/2x11
 Default Paper Type = Not Specified
 Paper Tray = Auto
 Output Tray = Elevate Tray
 Binding Position = Left Binding
 Double-Sided = Off
 Staple = Off
 Hole-Punch = Off
 Orientation = Portrait
 # of Sets = 1
 No Matching Paper in Tray Setting = Switch Trays (Tray Priority)
 Spool Setting = On
 Convert = On
 PDL Setting = Auto
 Banner Setting = Disable
 Banner Paper Tray = Auto
 Image Quality Setting = Document
 Glossy Mode = Off
 Toner Save = Off
 Edge Enhancement = Off

PCL Setting

Font Source = 1
 Font Number = 0
 Font Point = 12.00
 Font Pitch = 10.00
 Symbol Set = Roman-8
 Line/Page = 60 [Line / Page]
 CR/LF Mapping = Off
 Select Color = Auto Color
 Thin Line Support = On

PS Setting

Print Reports = Disable
 Text RGB Source = 4
 Text Destination Profile = Auto
 Image RGB Source = 4
 Image Destination Profile = Auto
 Graphics RGB Source = 4
 Graphics Destination Profile = Auto
 Simulation Profile = 21
 Select Color = Auto Color

XPS Settings

Verify XPS Digital Signature = Disable

Test Print

Configuration
 PCL Font List
 PS Font List
 Demo Page

I/F Setting

Network Rx Timeout = 60 [sec.]
 USB Timeout = 60 [sec.]
 Print XPS Errors = Enable

Installed

Printer Storage = Installed
 Printer Memory = 8192 [MByte]

Printer Information

Installed Tray

Tray 1 = 8 1/2x14
 Tray 2 = 11x17
 Tray 3 = 8 1/2x11
 Tray 4 = None
 LCT = None

Option

Duplex Unit = Installed
 Finisher = Available
 Punch Unit = Not Available
 Fold Unit = Not Available
 Fax Unit = Available
 Mailbin Unit = Not Available

Firmware Version

Management Version = 5
 Printer Controller = AA2J0Y0-3000-GC1-R7

Network

MAC Address

MAC Address = 00:50:AA:43:F2:FD

TCP/IP

TCP/IP = Enable
 IP Address = 192.168.254.48
 Subnet Mask = 255.255.255.0
 Default Gateway = 192.168.254.245
 RAW Port 0 = 9100
 RAW Port 1 = 9112
 RAW Port 2 = 9113
 RAW Port 3 = 9114
 RAW Port 4 = 9115
 RAW Port 5 = 9116

Netware

Netware = Disable

Appletalk

Appletalk = Disable

SMB

SMB = Disable